


Screener output	30 - 60 tons/hour	Trommel screener
Max bucket width	2000 mm	Screener suitable for small loaders with bucket width up to 200 cm / volume up to 1,5 m³, and excavators of total weight 10 to 20 tons.
Screening area	6,5 m²	
Power input	400 V / 4 kW	Suitable to be used with excavators: AT 315/317/320/M315/M316/M317/M318/M319/M320, JCB 140X/150X/160W/175W, LIEBHERR R914/R918/R920/A914/A916/A918/A920, KOMATSU, WB93/WB97/PW158/PW160/PW180/PC170, WACKER NEUSON ET145/EW100, VOLVO EC140/145/160/180/EW150/160/170/180
Weight	2000 kg	
Width (A)	1600 mm	
Length (B)	4430 mm	
Height (C)	2700 mm	





Suitable with loaders: WACKER NEUSON WL 52/54, BOBCAT L85, MECALAC AX1000/AS850/AS900/AF1050, JCB 3CX/407/409, KUBOTA R90, CAT 906/907, LIEBHERR L507/L508, KOMATSU WA 100, TEREX TL 100, YANMAR V 100, WEIDEMANN 5080, KRAMER 5095/8095/8105, VOLVO L30/L35, WEYCOR AR 400/AR420/480S

Optional Attachments:

- conveyor belts in lengths of 3, 4, 5 and 6 meters
- More fractions, it is possible to combine up to 3 different sieve sizes









Producer reserves all rights to change technical specification of the screeners without prior notice. Please, contact us at all times for exact technical details, such as transport dims and weights.